


ARVEX Grobelny Sp. z o.o.  
ul. Makuszyńskiego 4  
30-969 Kraków. POLAND

## WTZ/WTZB - Technical Specification

wood screw, wafer head, shank ribs,  
cut point (type 17), cut on thread, torx recess,  
yellow zinc plated (WTZ) or white zinc plated (WTZB)

16th November 2017



Note: 1. Material: C10B21 2. Bending angle: min 45°

Size [mm]	DK	K	H	KH	Q	UK	TORX
6.0	14.50-16.10	10.0-12.0	1.40-1.80	2.70-3.50	2.30-3.20	7.30-8.50	T 30
8.0	20.00-22.00	15.0-17.0	1.65-1.90	3.05-3.75	3.30-4.20	9.00-10.00	T 40
10.0	23.50-26.50	19.0-21.0	1.80-2.20	3.60-4.40	4.00-5.00	11.30-12.50	T 40

Size [mm]	D	d	P	SL	SB	E
6.0	5.80-6.10	3.80-4.15	4.30-5.00	9.50-10.50	4.60-5.00	4.15-4.35
8.0	7.80-8.10	5.10-5.50	5.00-5.80	11.00-13.00	6.80-7.20	5.70-5.90
10.0	9.70-10.15	6.00-6.50	6.00-7.00	11.00-13.00	7.60-8.20	6.85-7.25

L [mm]	6.0 mm	8.0 mm	10.0 mm
±2.0	LT ±1.5	LT ±1.5	LT ±1.5
40	20	FULL	
50	30	30	
60	35	35	
70	42		
80	50	50	50
90	50		
100	60	60	60
110	60		
120	60	60	60
130	70		
140	70	80	80
150	70		
160	70	80	80
180	70	80	80
200	70	80	80
220	70	80	80
240	70	80	80
260	70	80	80
280	70	80	80
300	70	80	80
320		80	80
340		80	80
360		80	80
380		80	80
400		80	80
420		100	
440		100	
450		100	