



| Arvex reference name | Outer diameter Φ [mm] | Total length L [mm] | Metric thread M [mm] | Sleeve #1 length L_1 [mm] | Sleeve #2 length L_2 [mm] | Thread #1 length f_1 [mm]* | Thread #2 length f_2 [mm]* | Sleeves' thickness t [mm] | Inner sleeve diameter d [mm] | Cone diameter S_c [mm] | Spanner size sk [mm] | Outer diameter of washer z [mm] | Clearance diameter of washer w [mm] | Comment |
|----------------------|----------------------------|---------------------|----------------------|-----------------------------|-----------------------------|------------------------------|------------------------------|---------------------------|------------------------------|--------------------------|----------------------|---------------------------------|-------------------------------------|----------------------------|
| SLR 12/80 M8 | 11.7 ^{+/-0.1} | 80 | M8 | 58 | / | 80 | | 1.20 ^{-0.05} | 9.2-9.5 | 12.0-12.2 | 13 | 18.2 | 8.4 | fully threaded, one sleeve |
| SLR 12/100 M8 | | 100 | | 35 | 43 | 40 | 40 | | | | | | | |
| SLR 12/120 M8 | | 120 | | 35 | 60 | 45 | 45 | | | | | | | |
| SLR 12/150 M8 | | 150 | | 35 | 90 | 55 | 55 | | | | | | | |
| SLR 12/180 M8 | | 180 | | 35 | 120 | 55 | 55 | | | | | | | |
| SLR 12/210 M8 | | 210 | | 35 | 150 | 70 | 70 | | | | | | | |

| Arvex reference name | Φ [mm] | L [mm] | M [mm] | L ₁ [mm] | L ₂ [mm] | f ₁ [mm]* | f ₂ [mm]* | t [mm] | d [mm] | S _c [mm] | sk [mm] | z [mm] | w [mm] | Comment |
|----------------------|------------------------|--------|--------|---------------------|---------------------|----------------------|----------------------|-----------------------|---------------|--------------------------|---------|--------|--------|----------------------------|
| SLR 12/250 M8 | 11.7 ^{+/-0.1} | 250 | M8 | 35 | 190 | 80 | 80 | 1.20 ^{-0.05} | 9.2-9.5 | 12.0-12.2 | 13 | 18.2 | 8.4 | |
| SLR 12/280 M8 | | 280 | | 35 | 220 | 90 | 90 | | | | | | | |
| SLR 12/300 M8 | | 300 | | 35 | 240 | 90 | 90 | | | | | | | |
| SLR 14/80 M10 | 13.7 ^{+/-0.1} | 80 | M10 | 57 | / | 80 | | 1.45 ^{-0.15} | 10.7 -11.2 | 14.0-14.2 | 17 | 22.7 | 10.5 | fully threaded, one sleeve |
| SLR 14/100 M10 | | 100 | | 40 | 37 | 40 | 40 | | | | | | | |
| SLR 14/120 M10 | | 120 | | 40 | 55 | 45 | 45 | | | | | | | |
| SLR 14/150 M10 | | 150 | | 40 | 85 | 55 | 55 | | | | | | | |
| SLR 14/180 M10 | | 180 | | 40 | 115 | 55 | 55 | | | | | | | |
| SLR 14/210 M10 | | 210 | | 40 | 145 | 70 | 70 | | | | | | | |
| SLR 14/250 M10 | | 250 | | 40 | 185 | 80 | 80 | | | | | | | |
| SLR 14/300 M10 | | 300 | | 40 | 235 | 80 | 80 | | | | | | | |
| SLR 14/400 M10 | | 400 | | 40 | 335 | 90 | 90 | | | | | | | |
| SLR 16/60 M10 | 15.7 ^{+/-0.1} | 60 | M10 | 35 | / | 60 | | 1.60 ^{-0.20} | 12.4 -13.0 | 16.0-16.2 | 17 | 22.7 | 10.5 | fully threaded, one sleeve |
| SLR 16/80 M10 | | 80 | | 55 | / | 80 | | | | | | | | fully threaded, one sleeve |
| SLR 16/100 M10 | | 100 | | 45 | 30 | 100 | | | | | | | | fully threaded |
| SLR 16/120 M10 | | 120 | | 45 | 50 | 45 | 45 | | | | | | | |
| SLR 16/150 M10 | | 150 | | 45 | 80 | 55 | 55 | | | | | | | |
| SLR 16/180 M10 | | 180 | | 45 | 110 | 55 | 55 | | | | | | | |
| SLR 16/210 M10 | | 210 | | 45 | 140 | 70 | 70 | | | | | | | |
| SLR 16/250 M10 | | 250 | | 45 | 180 | 80 | 80 | | | | | | | |
| SLR 16/300 M10 | | 300 | | 45 | 230 | 80 | 80 | | | | | | | |
| SLR 18/100 M12 | 17.7 ^{+/-0.1} | 100 | M12 | 50 | 22 | 100 | | 2.10 ^{-0.20} | 13.4 -14.0 | 18.0-18.2 | 19 | 28.3 | 13.0 | fully threaded |
| SLR 18/120 M12 | | 120 | | 50 | 40 | 45 | 45 | | | | | | | |
| SLR 18/140 M12 | | 140 | | 50 | 60 | 55 | 55 | | | | | | | |
| SLR 18/160 M12 | | 160 | | 50 | 80 | 55 | 55 | | | | | | | |
| SLR 18/180 M12 | | 180 | | 50 | 100 | 55 | 55 | | | | | | | |
| SLR 18/200 M12 | | 200 | | 50 | 120 | 70 | 70 | | | | | | | |
| SLR 18/250 M12 | | 250 | | 50 | 170 | 80 | 80 | | | | | | | |
| SLR 18/300 M12 | | 300 | | 50 | 220 | 80 | 80 | | | | | | | |
| SLR 24/120 M16 | 23.7 ^{+/-0.1} | 120 | M16 | 80 | / | 45 | 45 | 2.50 ^{-0.20} | 18.6 -19.2 | 24.2 (round, grooved) | 24 | 40.3 | 17.0 | one sleeve |
| SLR 24/140 M16 | | 140 | | 60 | 40 | 55 | 55 | | | | | | | |
| SLR 24/160 M16 | | 160 | | 60 | 60 | 55 | 55 | | | | | | | |
| SLR 24/180 M16 | | 180 | | 60 | 80 | 55 | 55 | | | | | | | |
| SLR 24/200 M16 | | 200 | | 60 | 100 | 70 | 70 | | | | | | | |
| SLR 24/250 M16 | | 250 | | 60 | 150 | 80 | 80 | | | | | | | |
| SLR 24/300 M16 | | 300 | | 60 | 200 | 80 | 80 | | | | | | | |

* minium values, longer thread allowed (also allowed fully threaded stud - f1 and f2 combined with no break in the middle)

Robert Grobelny
Kierownik Działu Sprzedaży
Sales Manager
ARVEX GROBELNY Sp. z o.o.
2020 NOV 4th